

Surface

Species¹ or Product

PREFINISHED

CYPRESS

**120mm Cover x 12mm Thick SOLID WOOD
FLOORING**

**Ready to Lay
NOTHING MORE TO DO**



Information provided is based on sample test averages and there will be variation from piece to piece.

Hardness (Janka Test)	6.5kN	Density	680 kg/m ³
Wide/Cover (mm)	120	Amount per Unit/Box ^[4]	2.02 Lineal Metres
Lengths ^[2] (mm)	2100	Formaldehyde Emission	'E1'
Thickness (mm)	12	Coating Gloss Level	35% SATIN
Packed ^[4]	8 pieces high x 1 wide	Coating	7 layers 125g/m2
Grade	Natural Knotty	Coating Wear Resistance ^[3]	
Scientific Name ^[1]	Callitris glauca	Moisture Content	9% to 13%

Suitable for relative humidity from 30% to 60%. See our document "[Moisture Management](#)" for more information.

FIRE RESISTANCE DATA: For **critical design** information see our document "[FIRE HAZARD REQUIREMENTS FOR TIMBER FLOORING](#)"

^[1] Species of recycled/waste recovery grade may include a range & are identified based on appearance and properties – See our document "[Sources of Wood](#)" for more information.

^[2] Lengths usually made up to 2100mm. Some combinations of lengths made up to as short as 1800mm are occasionally supplied.

^[3] Taber Test – See our document "[Floor Life](#)" for more information.

^[4] Sometimes square metres will vary to utilise all lengths. If you need exactly the indicated square metres please check with us.