

Surface

Species<sup>1</sup> or Product

**PREFINISHED**

**REDGUM**

**133.5mm Cover x 18mm Thick SOLID WOOD FLOORING**

**Ready to Lay  
NOTHING MORE TO DO**



Hardness (Janka Test)	12kN	Density	1050 kg/m <sup>3</sup>
Wide/Cover (mm)	133.5	Amount per Unit/Box <sup>[4]</sup>	1.68 Square Metres
Lengths <sup>[2]</sup> (mm)	2100	Formaldehyde Emission	'E0'(no emission)
Thickness (mm)	18	Coating Gloss Level	35% SATIN
Packed <sup>[4]</sup>	6 pieces high x 1 wide	Coating	7 layers 125g/m2
Grade	Recycled/Waste Recovery	Coating Wear Resistance <sup>[3]</sup>	
Scientific Name <sup>[1]</sup>	Eucalyptus tereticornis & others	Moisture Content	6% to 10%

Information provided is based on sample test averages and there will be variation from piece to piece.

Suitable for relative humidity from 30% to 60%. See our document "[Moisture Management](#)" for more information.

**FIRE RESISTANCE DATA:** For **critical design** information see our document "[FIRE HAZARD REQUIREMENTS FOR TIMBER FLOORING](#)"

**CRITICAL RADIANT FLUX** Greater than 4.5kW/m2 **Smoke Development Rate** less than 750%-min

<sup>[1]</sup> Species of recycled/waste recovery grade may include a range & are identified based on appearance and properties – See our document "[Sources of Wood](#)" for more information.

<sup>[2]</sup> Lengths usually made up to 2100mm. Some combinations of lengths made up to as short as 1800mm are occasionally supplied.

<sup>[3]</sup> Taber Test – See our document "[Floor Life](#)" for more information.

<sup>[4]</sup> Sometimes square metres will vary to utilise all lengths. If you need exactly the indicated square metres please check with us.